

TCR ADVANCED SL TEAM



SPECIFICATIONS / SPECIFICATIONS

FRAME	SIZES / TAILLES	XS, S, M, M/L, L, XL
	COLOURS / COULEURS	Composite/Silver
	FRAME / CADRE	Advanced SL-Grade Composite, Integrated Seatpost
COMPONENTS	FORK / FOURCHE	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
	SHOCK / AMORTISSEUR	N / A
	HANDLEBAR / CINTRE	PRO VIBE OS Composite, 31.8
	STEM / POTENCE	PRO PLT Composite 31.8mm, 10 deg
	SEATPOST / TIGE DE SELLE	Advanced SL-Grade Composite, Integrated Design
	SADDLE / SELLE	Selle Italia SLR-XP w/ Vanox rails
	PEDALS / PEDALES	Not Included
DRIVETRAIN	SHIFTERS / MANETTES	Shimano Dura-Ace 7900
	FR DERAILLEUR / DERAILLEUR AV.	Shimano Dura-Ace 7900
	RR DERAILLEUR / DERAILLEUR AR.	Shimano Dura-Ace 7900
	BRAKES / FREINS	Shimano Dura-Ace 7900
	BRAKE LEVERS / MANETTES DE FREIN	Shimano Dura-Ace 7900
	CASSETTE / CASSETTE	Shimano Dura-Ace 7900 12/25T 10-SPD
	CHAIN / CHAÎNE	Shimano Dura-Ace 7900
	CRANKSET / PEDALIER	Shimano Dura-Ace 7900, 39/52T
	BOTTOM BRACKET / BOÎTER DE PEDALIER	Shimano Dura-Ace, Internal Press Fit
	WHEELS	RIMS / JANTES
HUBS / MOYEUX		Shimano Dura-Ace carbon WH-7850-C24-CL
SPOKES / RAYONS		Shimano Dura-Ace carbon WH-7850-C24-CL
TIRES / PNEUS		Schwalbe Ultramo, 700X23C foldable
EXTRAS		2 ISP Clamps - Reg 20mm/XL 40mm



FEATURES / CARACTERISTIQUES

- Complete Shimano Dura-Ace 7900-series component group
- Shimano PRO composite handlebar and stem, Integrated seatpost
- Shimano Dura-Ace carbon composite wheelset, Schwalbe Ultramo tires

FRAME GEOMETRY / GEOMETRIE DU CADRE

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	299601	71.00	74.50	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	299602	72.00	73.50	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	299603	73.00	73.00	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	299604	73.00	72.00	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	299605	73.00	72.00	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	299606	73.00	72.00	60.5	20.0	40.5	102.1	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire